



US009638308B2

(12) **United States Patent**
Ishida

(10) **Patent No.:** **US 9,638,308 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **PULLEY STRUCTURE**

(75) Inventor: **Tomokazu Ishida**, Hyogo (JP)

(73) Assignee: **MITSUBOSHI BELTING LTD.**,
Hyogo (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 248 days.

(21) Appl. No.: **13/817,967**

(22) PCT Filed: **Aug. 30, 2011**

(86) PCT No.: **PCT/JP2011/069669**

§ 371 (c)(1),
(2), (4) Date: **Feb. 20, 2013**

(87) PCT Pub. No.: **WO2012/029815**

PCT Pub. Date: **Mar. 8, 2012**

(65) **Prior Publication Data**

US 2013/0150191 A1 Jun. 13, 2013

(30) **Foreign Application Priority Data**

Aug. 31, 2010 (JP) 2010-193935

(51) **Int. Cl.**

F16H 55/36 (2006.01)

F16D 7/02 (2006.01)

F16F 15/123 (2006.01)

(52) **U.S. Cl.**

CPC **F16H 55/36** (2013.01); **F16D 7/028**
(2013.01); **F16F 15/123** (2013.01); **F16H**
2055/366 (2013.01)

(58) **Field of Classification Search**

CPC **F16H 55/36**; **F16H 2055/366**; **F16H 55/02**;
F16H 55/06; **F16H 55/14**; **F16H 7/1218**;

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2008/0108442 A1* 5/2008 Jansen F16D 3/52
464/54

2010/0147646 A1 6/2010 Lannutti et al.

FOREIGN PATENT DOCUMENTS

DE 10012233 A1 9/2001

EP 1754914 A1 2/2007

(Continued)

OTHER PUBLICATIONS

International Search Report (PCT/ISA/210 and PCT/ISA/220)
dated Nov. 22, 2011 from the International Searching Authority in
counterpart application No. PCT/JP/2011/069669.

(Continued)

Primary Examiner — William E Dondero

Assistant Examiner — Juan Campos, Jr.

(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

(57)

ABSTRACT

A drive pulley structure has a cylindrical pulley member, a
hub structure that is provided inside the pulley member so as
to rotate relative to the pulley member, a coil spring that is
fixed to the hub structure, a tapering which has a conical
round surface as of a cone whose axis is made up of a
rotational axis J of the hub structure, and a frictional member
that is inserted to be interposed between the conical round
surface of the tapering and the pulley member, and the coil
spring is inserted to be interposed in place while being
compressed in the direction of the rotational axis of the hub
structure, the tapering, the frictional member and the pulley
member being brought into press contact with each other by
virtue of a restoring force P of the coil spring.

6 Claims, 7 Drawing Sheets

